

MODLINK MSDD SINGLE COMBI INSERT GERMANY

1x RJ45 + 1x data cutout

- 1x Germany (VDE) white
- 1x RJ45, 8-pole metal, CAT6A (female/female)
- 1x RJ45 cut-out

Link naar het product

Afbeelding



Product van afwijken van afbeelding



Commerciële gegevens

|                      |               |
|----------------------|---------------|
| ECLASS-6.0           | 27189217      |
| ECLASS-6.1           | 27189217      |
| ECLASS-7.0           | 27189217      |
| ECLASS-8.0           | 27189217      |
| ECLASS-9.0           | 27182806      |
| ECLASS-10.1          | 27182806      |
| ECLASS-11.1          | 27182806      |
| ECLASS-12.0          | 27182806      |
| ETIM-5.0             | EC002625      |
| Douane tarief nummer | 85366990      |
| GTIN                 | 4048879600880 |
| Verpakkingseenheid   | 1             |

Device protection | Electrical

|                                     |      |
|-------------------------------------|------|
| Degree of protection (EN IEC 60529) | IP20 |
|-------------------------------------|------|

Mechanical data | Mounting data

|        |         |
|--------|---------|
| Height | 87,5 mm |
| Width  | 50,7 mm |
| Depth  | 43 mm   |

Environmental characteristics | Climatic

|                            |       |
|----------------------------|-------|
| Operating temperature min. | -5 °C |
| Operating temperature max. | 50 °C |

|                          |        |
|--------------------------|--------|
| Storage temperature min. | -10 °C |
|--------------------------|--------|

|                          |       |
|--------------------------|-------|
| Storage temperature max. | 60 °C |
|--------------------------|-------|

**Shielding plate**

|                        |                  |
|------------------------|------------------|
| Connection information | Threaded hole M4 |
|------------------------|------------------|

|                   |        |
|-------------------|--------|
| Tightening torque | 0,9 Nm |
|-------------------|--------|

**Germany (VDE)**

|                               |                     |
|-------------------------------|---------------------|
| Connection cross section max. | 2,5 mm <sup>2</sup> |
|-------------------------------|---------------------|

|                 |    |
|-----------------|----|
| AWG number max. | 14 |
|-----------------|----|

|                      |       |
|----------------------|-------|
| Operating voltage AC | 250 V |
|----------------------|-------|

|                   |      |
|-------------------|------|
| Operating current | 16 A |
|-------------------|------|

|            |                           |
|------------|---------------------------|
| Connection | Spring clamp terminals FK |
|------------|---------------------------|

|              |        |
|--------------|--------|
| No. of poles | 2 + PE |
|--------------|--------|

|                      |   |
|----------------------|---|
| Connections per pole | 2 |
|----------------------|---|

|                            |     |
|----------------------------|-----|
| Protection contact present | yes |
|----------------------------|-----|

**RJ45**

|                                       |      |
|---------------------------------------|------|
| Operating voltage AC max. (UL-listed) | 30 V |
|---------------------------------------|------|

|                                       |        |
|---------------------------------------|--------|
| Operating voltage DC max. (UL-listed) | 42,4 V |
|---------------------------------------|--------|

|                             |        |
|-----------------------------|--------|
| Current operating max. (UL) | 175 mA |
|-----------------------------|--------|

|                          |      |
|--------------------------|------|
| Family construction form | RJ45 |
|--------------------------|------|

|                       |      |
|-----------------------|------|
| Family type Back side | RJ45 |
|-----------------------|------|

|                     |       |
|---------------------|-------|
| Cable category min. | Cat6a |
|---------------------|-------|

|                    |                   |
|--------------------|-------------------|
| Looking techniques | Snap-in connector |
|--------------------|-------------------|