

**M12 male 0° / M12 female 0° A-cod. V4A**

PUR AWG24+22 shielded vt UL/CSA+drag ch. 7.5m

M12 – M12, 5-pole

Male straight – female straight

A-coded


Stainless steel 1.4404 (V4A)

Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Link naar het product](#)**Afbeelding**



Product van afwijken van afbeelding



|                                     |                   |
|-------------------------------------|-------------------|
| Cable length                        | 7,5 m             |
| Side 1                              |                   |
| Tightening torque                   | 0,6 Nm            |
| Mounting method                     | inserted, screwed |
| Coating contact                     | gold plated       |
| Family construction form            | M12               |
| Thread                              | M12 x 1           |
| Coding                              | A                 |
| Material contact                    | Copper alloy      |
| No. of poles                        | 5                 |
| Width across flats                  | SW13              |
| Degree of protection (EN IEC 60529) | IP65, IP67        |
| Side 2                              |                   |
| Tightening torque                   | 0,6 Nm            |
| Mounting method                     | inserted, screwed |
| Coating contact                     | gold plated       |
| Family construction form            | M12               |
| Thread                              | M12 x 1           |
| Coding                              | A                 |
| Material contact                    | Copper alloy      |
| No. of poles                        | 5                 |
| Commerciële gegevens                |                   |
| ECLASS-6.0                          | 27279218          |
| ECLASS-7.0                          | 27279218          |
| ECLASS-8.0                          | 27279218          |
| ECLASS-9.0                          | 27060311          |
| ECLASS-10.1                         | 27060307          |
| ECLASS-11.1                         | 27060307          |
| ECLASS-12.0                         | 27060307          |
| ETIM-5.0                            | EC001855          |
| Douane tarief nummer                | 85444290          |
| GTIN                                | 4048879412612     |

Verpakkingseenheid 1

**Electrical data | Supply**

|                                    |      |
|------------------------------------|------|
| Operating voltage AC max.          | 60 V |
| Operating voltage DC max.          | 60 V |
| Operating voltage AC (UL-listed)   | 30 V |
| Operating voltage DC (UL-listed)   | 30 V |
| Current operating per contact max. | 4 A  |

**Diagnostics**

|                       |    |
|-----------------------|----|
| Status indication LED | no |
|-----------------------|----|

**Device protection | Electrical**

|                                        |                   |
|----------------------------------------|-------------------|
| Additional condition protection degree | inserted, screwed |
| Pollution Degree                       | 3                 |
| Rated surge voltage                    | 1,5 kV            |
| Material group (IEC 60664-1)           | I                 |

**Mechanical data**

|                             |         |
|-----------------------------|---------|
| Contour for corrugated hose | without |
|-----------------------------|---------|

**Mechanical data | Material data**

|                  |                              |
|------------------|------------------------------|
| Material gasket  | FKM                          |
| Material housing | PUR                          |
| Locking material | Stainless steel 1.4404 (V4A) |

**Mechanical data | Mounting data**

|                 |                                       |
|-----------------|---------------------------------------|
| Mounting method | inserted, screwed, Shaking protection |
|-----------------|---------------------------------------|

**Environmental characteristics | Climatic**

|                                        |                            |
|----------------------------------------|----------------------------|
| Operating temperature min.             | -25 °C                     |
| Operating temperature max.             | 85 °C                      |
| Additional condition temperature range | depending on cable quality |

**Conformity**

|                  |                          |
|------------------|--------------------------|
| Product standard | DIN EN 61076-2-101 (M12) |
|------------------|--------------------------|

**Installation | Cable**

|                                   |                                                                |
|-----------------------------------|----------------------------------------------------------------|
| Cable identification              | 803                                                            |
| Jacket Color                      | violet                                                         |
| Type of Certificate               | cURus                                                          |
| Amount stranding                  | 1                                                              |
| Stranding                         | 2 wires twisted                                                |
| Amount stranding (type 2)         | 1                                                              |
| Stranding (type 2)                | 2 Stranded joints twisted                                      |
| Cable shielding (type)            | copper braid, tinned                                           |
| Cable shielding (coverage)        | 65 %                                                           |
| Banding                           | Foil                                                           |
| Drain wire (cross-section)        | 22 AWG                                                         |
| wire arrangement                  | (white, blue), (black, red)                                    |
| No. of bending cycles (C-track)   | 1 Mio.                                                         |
| Cable weight                      | 63,12 g/m                                                      |
| Material jacket                   | PUR                                                            |
| Shore hardness jacket             | 90 ± 5 Shore A                                                 |
| Freedom from ingredients (jacket) | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free |
| Outer-diameter (jacket)           | 6,9 mm                                                         |
| Tolerance outer diameter (sheath) | ± 5 %                                                          |
| Material wire insulation          | PE                                                             |
| Amount wires                      | 2                                                              |

|                                                 |                                                      |
|-------------------------------------------------|------------------------------------------------------|
| Outer diameter insulation                       | 2,1 mm                                               |
| Outer diameter tolerance core insulation        | ± 5 %                                                |
| Shore hardness wire insulation                  | 64 ± 5 Shore D                                       |
| Ingredient freeness wire insulation             | lead-free, CFC-free, halogen-free                    |
| Amount strands (wire)                           | 19                                                   |
| Diameter of single wires                        | 24 AWG                                               |
| Conductor crosssection (wire)                   | 24 AWG                                               |
| Drain wire (cross-section)                      | 22 AWG                                               |
| Material conductor wire                         | copper stranded wire, tinned                         |
| Electrical function wire                        | Data                                                 |
| Material wire insulation (Data)                 | PE                                                   |
| Outer diameter wire insulation (Data)           | 1,5 mm                                               |
| Tolerance outer diameter wire insulation (data) | ± 53 %                                               |
| Ingredient freeness wire insulation (Data)      | lead-free, CFC-free, halogen-free                    |
| Amount wires (Data)                             | 2                                                    |
| Amount strands wire (Data)                      | 19                                                   |
| Diameter of single wires (Data)                 | 22 AWG                                               |
| Conductor crosssection wire (Data)              | 22 AWG                                               |
| Material conductor wire (Data)                  | copper stranded wire, tinned                         |
| Electrical function wire (data)                 | Power                                                |
| Traversing distance (C-track)                   | 5 m                                                  |
| Current load capacity (standard)                | to DIN VDE 0298-4                                    |
| Current load capacity min. wire                 | 4,5 A                                                |
| Current load capacity min. Wire (Data)          | 6 A                                                  |
| Electrical function wire                        | Data                                                 |
| Electrical function wire (data)                 | Power                                                |
| Characteristic impedance                        | 120 Ω ± 10 % @ 1 MHz                                 |
| Electrical resistance line constant wire        | 78 Ω/km                                              |
| Electrical resistance coating wire (Data)       | 54 Ω/km                                              |
| Nominal voltage power AC max.                   | 300 V                                                |
| Electric capacitance (power)                    | 40000 pF/km                                          |
| AC withstand voltage power (wire - shield)      | 2 kV @ 60 s                                          |
| AC withstand voltage power (wire - wire)        | 2 kV @ 60 s                                          |
| Min. operating temperature (static)             | -40 °C                                               |
| Max. operating temperature (fixed)              | 80 °C                                                |
| Operating temperature min. (dynamic)            | -30 °C                                               |
| Operating temperature max. (dynamic)            | 70 °C                                                |
| Flame resistance                                | UL 1581 § 1100 FT2   IEC 60332-2-2   UL 1581 § 1090  |
| chemical resistance                             | Good, application-related testing                    |
| Gasoline resistance                             | Good, application-related testing                    |
| Oil resistance                                  | DIN EN 60811-404   Good, application-related testing |
| Bending radius (installation)                   | x Outer diameter                                     |
| Bending radius (fixed)                          | 6 x Outer diameter                                   |
| Bending radius (dynamic)                        | 10 x Outer diameter                                  |
| No. of torsion cycles                           | 2 Mio.                                               |
| Torsion speed                                   | 35 cycles/min                                        |
| Torsion stress                                  | ± 30 °/m                                             |