

MOTOR SUPPRESSOR

RC, 3x575VAC/7,5kW

3× 575 V AC

RC

Suppressors for other voltages, frequencies, and motor ratings available on request. Do not use RC motor suppressors with frequency inverters.

[Link to Product](#)

Illustration



Product may differ from Image



| Commercial data |          |
|-----------------|----------|
| ECLASS-6.0      | 27371013 |
| ECLASS-6.1      | 27371013 |
| ECLASS-7.0      | 27371013 |
| ECLASS-8.0      | 27371013 |
| ECLASS-9.0      | 27371013 |
| ECLASS-10.1     | 27371013 |

|                                                      |                                                      |
|------------------------------------------------------|------------------------------------------------------|
| ECLASS-11.1                                          | 27371013                                             |
| ECLASS-12.0                                          | 27371013                                             |
| ETIM-5.0                                             | EC000197                                             |
| customs tariff number                                | 85363010                                             |
| GTIN                                                 | 4048879019613                                        |
| Packaging unit                                       | 1                                                    |
| <b>Electrical data   Supply</b>                      |                                                      |
| Power frequency                                      | 50 ... 60 Hz                                         |
| <b>Electrical data   Input</b>                       |                                                      |
| Input voltage AC                                     | 575 V                                                |
| <b>Installation</b>                                  |                                                      |
| Connection cross-section stranded/fine-stranded min. | 0,5 mm <sup>2</sup>                                  |
| <b>Installation   Connection</b>                     |                                                      |
| Connection information                               | Einzellitzen mit selbstsicherndem Gabelkabelschuh M4 |
| Length single strands                                | 250 mm                                               |
| <b>Device protection   Media</b>                     |                                                      |
| Flame resistance                                     | flame retardant                                      |
| <b>Mechanical data   Material data</b>               |                                                      |
| Combustibility class housing (UL94)                  | V-0                                                  |
| Material housing                                     | Plastic                                              |
| Material potting compound                            | 2-component epoxy                                    |
| <b>Mechanical data   Mounting data</b>               |                                                      |
| Height                                               | 75 mm                                                |
| Width                                                | 45 mm                                                |
| Depth                                                | 42 mm                                                |
| <b>Environmental characteristics   Climatic</b>      |                                                      |
| Operating temperature min.                           | -20 °C                                               |
| Operating temperature max.                           | 60 °C                                                |