

UFL 10 L PLUG FOR SIGNAL TRANSFER

24 VDC / 1 A - male with LED

Ribbon cable connector + LED

10-pole

Via the combined fixing mechanism, connectors with or without strain relief can be connected.  
for plugs with or without strain relief (DIN 41651); for plugs with strain relief, it may be necessary to remove the bottom hook

Link to Product

Illustration



Product may differ from Image



| Commercial data |          |
|-----------------|----------|
| ECLASS-6.0      | 27141120 |
| ECLASS-6.1      | 27141120 |
| ECLASS-7.0      | 27141120 |
| ECLASS-8.0      | 27141120 |
| ECLASS-9.0      | 27141120 |

|                       |               |
|-----------------------|---------------|
| ECLASS-10.1           | 27141120      |
| ECLASS-11.1           | 27141120      |
| ECLASS-12.0           | 27141120      |
| ETIM-5.0              | EC001283      |
| customs tariff number | 85366990      |
| GTIN                  | 4048879026611 |
| Packaging unit        | 1             |

**Electrical data | Supply**

|                        |      |
|------------------------|------|
| Operating voltage AC   | 24 V |
| Operating current max. | 1 A  |

**Diagnostics**

|                       |     |
|-----------------------|-----|
| Status indication LED | red |
|-----------------------|-----|

**Device protection | Electrical**

|                                   |    |
|-----------------------------------|----|
| Overvoltage category (EN 60664-1) | II |
|-----------------------------------|----|

**Mechanical data | Mounting data**

|                            |                           |
|----------------------------|---------------------------|
| Mounting method            | geschnappt                |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height                     | 63 mm                     |
| Width                      | 50 mm                     |
| Depth                      | 48 mm                     |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C  |