

**MODLINK MSDD SOCKET INSERT FRANCE**

250VAC/16A orange

France (UTE-NF) orange  
for installing in front of main switch  
Spring clamp terminals

[Link to Product](#)

Illustration



Product may differ from Image



| Commercial data                          |               |
|------------------------------------------|---------------|
| ECLASS-6.0                               | 27189217      |
| ECLASS-6.1                               | 27189217      |
| ECLASS-7.0                               | 27189217      |
| ECLASS-8.0                               | 27189217      |
| ECLASS-9.0                               | 27182806      |
| ECLASS-10.1                              | 27182806      |
| ECLASS-11.1                              | 27182806      |
| ECLASS-12.0                              | 27182806      |
| ETIM-5.0                                 | EC000020      |
| customs tariff number                    | 85366990      |
| GTIN                                     | 4048879038157 |
| Packaging unit                           | 1             |
| Mechanical data   Mounting data          |               |
| Height                                   | 88 mm         |
| Width                                    | 51 mm         |
| Depth                                    | 33 mm         |
| Environmental characteristics   Climatic |               |
| Storage temperature min.                 | -10 °C        |
| Storage temperature max.                 | 60 °C         |
| France (UTE-NF)                          |               |
| Connection cross section max.            | 2,5 mm²       |

|                            |                           |
|----------------------------|---------------------------|
| AWG number max.            | 14                        |
| Operating voltage AC       | 250 V                     |
| Operating current min.     | 10 A                      |
| Operating current max.     | 16 A                      |
| Connection                 | Spring clamp terminals FK |
| No. of poles               | 2 + PE                    |
| Connections per pole       | 2                         |
| Protection contact present | yes                       |