

MODLINK MSDD CABLE ENTRY SYSTEM

KDP/R

round (M50)  
For sale only in packing units  
Cable diameter (7)× 3...6.5 mm, (1)× 6...10 mm

Link to Product

Illustration



Product may differ from Image

| Commercial data                         |                     |
|-----------------------------------------|---------------------|
| ECLASS-6.0                              | 27189217            |
| ECLASS-6.1                              | 27400604            |
| ECLASS-7.0                              | 27400604            |
| ECLASS-8.0                              | 27400604            |
| ECLASS-9.0                              | 27400604            |
| ECLASS-10.1                             | 27400604            |
| ECLASS-11.1                             | 27400604            |
| ECLASS-12.0                             | 27400604            |
| ETIM-5.0                                | EC000211            |
| customs tariff number                   | 39269097            |
| GTIN                                    | 4048879031615       |
| Packaging unit                          | 1                   |
| Device protection   Electrical          |                     |
| Degree of protection (EN IEC 60529)     | IP65                |
| Mechanical data   Material data         |                     |
| Material housing                        | PA                  |
| Mechanical data   Mounting data         |                     |
| Mounting method                         | screwed, geschnappt |
| Sheet thickness min. (snap-on mounting) | 1,5 mm              |
| Sheet thickness max. (snap-on mounting) | 2 mm                |
| Sheet thickness min. (screw mounting)   | 1,5 mm              |
| Sheet thickness max. (screw mounting)   | 2 mm                |
| Height                                  | 33 mm               |
| Width                                   | 58 mm               |
| Depth                                   | 58 mm               |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -30 °C |
| Operating temperature max. | 70 °C  |