



EXACT8, 8XM8, 3 POLE

Conn.M12 12 pole


8-way, 3-pole
M12 (12-pole)
Inline face or side mounting
Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration



Product may differ from Image



| Commercial data | |
|-----------------|----------|
| ECLASS-6.0 | 27143423 |
| ECLASS-6.1 | 27279219 |
| ECLASS-7.0 | 27279219 |
| ECLASS-8.0 | 27279219 |

| | |
|-----------------------|---------------|
| ECLASS-9.0 | 27440111 |
| ECLASS-10.1 | 27440111 |
| ECLASS-11.1 | 27440111 |
| ECLASS-12.0 | 27440111 |
| ETIM-5.0 | EC002585 |
| customs tariff number | 85369010 |
| GTIN | 4048879054515 |
| Packaging unit | 1 |

Electrical data | Supply

| | |
|------------------------------------|-------|
| Operating voltage DC | 24 V |
| Current operating per contact max. | 1,5 A |

Device protection | Electrical

| | |
|--|------------------|
| Degree of protection (EN IEC 60529) | IP67 |
| Additional condition protection degree | screwed, mounted |

Device protection | Media

| | |
|------------------|-----------------|
| Flame resistance | flame retardant |
|------------------|-----------------|

Mechanical data | Material data

| | |
|------------------|---------|
| Material housing | Plastic |
|------------------|---------|

Environmental characteristics | Climatic

| | |
|--|----------------------------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C |
| Additional condition temperature range | depending on cable quality |

Connection type 2

| | |
|--------------------------|---------|
| Family construction form | M12 |
| Gender | male |
| Color contact carrier | black |
| Coding | A |
| No. of poles | 12 |
| PIN 1 | 24 V DC |
| PIN 2 | 0 V |
| PIN 3 | S 1 |
| PIN 4 | S 2 |
| PIN 5 | S 3 |
| PIN 6 | S 4 |
| PIN 7 | S 5 |
| PIN 8 | S 6 |
| PIN 9 | S 7 |
| PIN 10 | S 8 |
| PIN 11 | S 9 |
| PIN 12 | S 10 |
| Family construction form | M8 |
| Gender | female |
| Color contact carrier | black |
| Coding | A |
| No. of poles | 3 |
| PIN 1 | + |
| PIN 3 | - |
| PIN 4 | S |