

SUPPRESSOR FOR SIEMENS CONTACTOR

Diode, 24...240 VDC, 15 W

24...240 V DC  
Varistor + Diode  
For other configurations and voltages, please inquire.

[Link naar het product](#)

Afbeelding



Product van afwijken van afbeelding



| Commerciële gegevens |          |
|----------------------|----------|
| ECLASS-6.0           | 27371013 |
| ECLASS-6.1           | 27371013 |
| ECLASS-7.0           | 27371013 |
| ECLASS-8.0           | 27371013 |
| ECLASS-9.0           | 27371013 |
| ECLASS-10.1          | 27371013 |
| ECLASS-11.1          | 27371013 |

|                                                 |                                  |
|-------------------------------------------------|----------------------------------|
| ECLASS-12.0                                     | 27371013                         |
| ETIM-5.0                                        | EC002498                         |
| Douane tarief nummer                            | 85363010                         |
| GTIN                                            | 4048879018579                    |
| Verpakkingseenheid                              | 1                                |
| <b>Compatibility   Compatible with</b>          |                                  |
| Appropriate contactors                          | 3 TH 2; 3 TF 2; 3 TH 20; 3 TF 20 |
| <b>Electrical data</b>                          |                                  |
| Damping factor                                  | 1.5× UN                          |
| <b>Electrical data   Input</b>                  |                                  |
| Input voltage DC min.                           | 24 V                             |
| Input voltage DC max.                           | 240 V                            |
| <b>Installation   Connection</b>                |                                  |
| Connection information                          | Plug contact                     |
| <b>Device protection   Media</b>                |                                  |
| Flame resistance                                | flame retardant                  |
| <b>Mechanical data   Material data</b>          |                                  |
| Combustibility class housing (UL94)             | V-0                              |
| Material housing                                | Plastic                          |
| <b>Mechanical data   Mounting data</b>          |                                  |
| Height                                          | 19,5 mm                          |
| Width                                           | 20 mm                            |
| Depth                                           | 24,5 mm                          |
| <b>Environmental characteristics   Climatic</b> |                                  |
| Operating temperature min.                      | -20 °C                           |
| Operating temperature max.                      | 70 °C                            |