

MKN POWER SUPPLY 1-PHASE, LINEAR REGULATED

IN: 230VAC OUT: 24V/0,07ADC

INPUT: 230 V AC  
OUTPUT: 24 V DC  
Current: 70 mA  
This power supply units meet the (EN 61000-3-2) standard for harmonic current.  
Condensation not permitted

[Link naar het product](#)

Afbeelding



Product van afwijken van afbeelding



| Commerciële gegevens |          |
|----------------------|----------|
| ECLASS-6.0           | 27049002 |
| ECLASS-6.1           | 27049002 |
| ECLASS-7.0           | 27049002 |
| ECLASS-8.0           | 27049002 |
| ECLASS-9.0           | 27040701 |

|                      |               |
|----------------------|---------------|
| ECLASS-10.1          | 27040701      |
| ECLASS-11.1          | 27040701      |
| ECLASS-12.0          | 27040701      |
| ETIM-5.0             | EC002540      |
| Douane tarief nummer | 85044095      |
| GTIN                 | 4048879079662 |
| Verpakkingseenheid   | 1             |

**Electrical data | Supply**

|                 |              |
|-----------------|--------------|
| Power frequency | 50 ... 60 Hz |
|-----------------|--------------|

**Electrical data | Input**

|                                      |         |
|--------------------------------------|---------|
| Characteristic back-up fuse          | Inertia |
| Input voltage AC min.                | 207 V   |
| Input voltage AC max.                | 253 V   |
| Input current                        | 10 mA   |
| External back-up fuse per phase max. | 0,063 A |

**Electrical data | Output**

|                     |                          |
|---------------------|--------------------------|
| Output suppression  | Screening capacitor, VDR |
| Output current max. | 0,07 A                   |
| Ripple (s-s) max.   | 10 mV                    |

**Device protection | Electrical**

|                                 |     |
|---------------------------------|-----|
| Overload protection output      | yes |
| Short-circuit protection output | yes |

**Mechanical data | Mounting data**

|                            |                                     |
|----------------------------|-------------------------------------|
| Mounting method            | geschnappt                          |
| Suitable for mounting type | Mounting rail TH35, G32, (EN 60715) |

**Environmental characteristics | Climatic**

|                            |       |
|----------------------------|-------|
| Operating temperature min. | 0 °C  |
| Operating temperature max. | 60 °C |

**Conformity**

|                  |                                    |
|------------------|------------------------------------|
| Product standard | EN 61558-2-6, EN 62041 category II |
| EMC              | EN 55011 B, EN 61000-3-2           |