


AS-INTERFACE VALVE PLUG PLUG

2 digital inputs, 2 digital outputs

Digital inputs/outputs
DI2 - 0.2 A (M12)
DO2 - 2 A (Form BI/M12)
24 V DC external (18...30.2 V DC) EN 61131-2, connection via black AS-Interface profile cable

Link naar het product

Afbeelding



Product van afwijken van afbeelding

Commerciële gegevens

ECLASS-6.0	27242604
ECLASS-6.1	27242604
ECLASS-7.0	27242604
ECLASS-8.0	27242604
ECLASS-9.0	27242604
ECLASS-10.1	27242604
ECLASS-11.1	27242604
ECLASS-12.0	27242604
ETIM-5.0	EC001599
Douane tarief nummer	85176200
GTIN	4048879046558
Verpakkingseenheid	1

Electrical data | Supply

Bus voltage AS-Interface DC min.	26,5 V
Bus voltage AS-Interface DC max.	31,6 V
Current consumption AS-i port max.	250 mA
Total current max.	2 A

Electrical data | Input

Overload resistant	yes
Short-circuit protected	yes
Type input	PNP, for 3-wire sensors or mechanical switches
Current carrying capacity max.	0,2 A

Electrical data | Output

Overload resistant	yes
--------------------	-----

Short-circuit protected	yes
-------------------------	-----

Output current per pin max.	2 A
-----------------------------	-----

Industrial communication | Bus data

Address range min.	1
--------------------	---

Address range max.	31
--------------------	----

Address setting type	Addressing socket
----------------------	-------------------

Industrial communication | AS-Interface

Profile (IO.ID.ID2)	S-3.F.E
---------------------	---------

Diagnostics

Diagnostic	No voltage
------------	------------

Diagnostic via LED	per module
--------------------	------------

LED display	Ethernet connection/data traffic
-------------	----------------------------------

Installation

Contact distance	11 mm
------------------	-------

Installation | Connection

Family construction form	M12
--------------------------	-----

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP67
-------------------------------------	------

Mechanical data | Mounting data

Height	68 mm
--------	-------

Width	33 mm
-------	-------

Depth	66 mm
-------	-------

Environmental characteristics | Climatic

Operating temperature min.	-20 °C
----------------------------	--------

Operating temperature max.	70 °C
----------------------------	-------