

**MODLINK MSDD DATA INSERT**

1xUSB-A female/female + 1xRJ45

USB (form A); RJ45  
1× USB 3.0 (female/female) form A  
1× RJ45, 8-pole metal, CAT5e (female/female)

[Link naar het product](#)

Afbeelding



Product van afwijken van afbeelding



Commerciële gegevens

|                      |               |
|----------------------|---------------|
| ECLASS-6.0           | 27189217      |
| ECLASS-6.1           | 27189217      |
| ECLASS-7.0           | 27189217      |
| ECLASS-8.0           | 27189217      |
| ECLASS-9.0           | 27189217      |
| ECLASS-10.1          | 27182806      |
| ECLASS-11.1          | 27182806      |
| ECLASS-12.0          | 27182806      |
| ETIM-5.0             | EC002625      |
| Douane tarief nummer | 85366990      |
| GTIN                 | 4048879037587 |
| Verpakkingseenheid   | 1             |

Mechanical data | Mounting data

|        |         |
|--------|---------|
| Height | 88 mm   |
| Width  | 51 mm   |
| Depth  | 70,4 mm |

Environmental characteristics | Climatic

|                          |       |
|--------------------------|-------|
| Storage temperature min. | 5 °C  |
| Storage temperature max. | 40 °C |

Shielding plate

|                        |                  |
|------------------------|------------------|
| Connection information | Threaded hole M4 |
|------------------------|------------------|

Tightening torque 0,9 Nm

**USB**

|                                       |                   |
|---------------------------------------|-------------------|
| Operating voltage AC                  | 48 V              |
| Operating voltage DC                  | 48 V              |
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Operating current                     | 1,5 A             |
| USB specification                     | 3.0               |
| Data transmission rate max.           | 5000 MBit/s       |
| Looking techniques                    | Snap-in connector |

**RJ45**

|                                       |                   |
|---------------------------------------|-------------------|
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Current operating max. (UL)           | 175 mA            |
| Family construction form              | RJ45              |
| Family type Back side                 | RJ45              |
| Cable category min.                   | Cat5e             |
| Looking techniques                    | Snap-in connector |