

MODLINK MSDD DATA INSERT

1×SUB-D25 female/male + 2×PS2 female/soldering

PS2; PS2; SUB-D25  
2× PS2 (6-pole solder connection)  
1× SUB-D25 (female/male)

Link naar het product

Afbeelding



Product van afwijken van afbeelding



Commerciële gegevens

|                      |               |
|----------------------|---------------|
| ECLASS-6.0           | 27189217      |
| ECLASS-6.1           | 27189217      |
| ECLASS-7.0           | 27189217      |
| ECLASS-8.0           | 27189217      |
| ECLASS-9.0           | 27182806      |
| ECLASS-10.1          | 27182806      |
| ECLASS-11.1          | 27182806      |
| ECLASS-12.0          | 27182806      |
| ETIM-5.0             | EC002625      |
| Douane tarief nummer | 85366990      |
| GTIN                 | 4048879037488 |
| Verpakkingseenheid   | 1             |

Mechanical data | Mounting data

|        |       |
|--------|-------|
| Height | 88 mm |
| Width  | 51 mm |
| Depth  | 15 mm |

Environmental characteristics | Climatic

|                          |       |
|--------------------------|-------|
| Storage temperature min. | 5 °C  |
| Storage temperature max. | 40 °C |

SUB-D9

|                      |      |
|----------------------|------|
| Operating voltage AC | 48 V |
|----------------------|------|

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 3 A                                            |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | SUB-D9                                         |
| Family type Back side                 | SUB-D9                                         |
| Gender                                | female                                         |
| Gender Rear                           | male                                           |
| Looking techniques                    | Standard UNC 4-40 screw thread bolt (EN 60807) |
| No. of poles                          | 9                                              |

**SUB-D25**

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 3 A                                            |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | SUB-D25                                        |
| Family type Back side                 | SUB-D25                                        |
| Gender                                | female                                         |
| Gender Rear                           | male                                           |
| Looking techniques                    | Standard UNC 4-40 screw thread bolt (EN 60807) |
| No. of poles                          | 25                                             |

**PS2**

|                               |                     |
|-------------------------------|---------------------|
| Connection cross section max. | 0,5 mm <sup>2</sup> |
| AWG number max.               | 20                  |
| Operating voltage AC          | 30 V                |
| Operating voltage DC          | 30 V                |
| Operating current             | 1 A                 |
| Family construction form      | PS2                 |
| Family type Back side         | PS2                 |
| Gender                        | female              |
| Gender Rear                   | Lötanschluss        |
| Looking techniques            | Screw locking       |
| No. of poles                  | 6                   |