

Signal tower Modlight70 Pro equipped with LED modules

blue,green,amber,red,buzzer

Basis, buzzer, LED modules  
red, yellow, green, blue

Link naar het product

Afbeelding



Product van afwijken van afbeelding



Commerciële gegevens

|                      |               |
|----------------------|---------------|
| ECLASS-6.0           | 27371230      |
| ECLASS-6.1           | 27371230      |
| ECLASS-7.0           | 27371230      |
| ECLASS-8.0           | 27371230      |
| ECLASS-9.0           | 27371230      |
| ECLASS-10.1          | 27371230      |
| ECLASS-11.1          | 27371230      |
| ECLASS-12.0          | 27371230      |
| ETIM-5.0             | EC001042      |
| Douane tarief nummer | 85318070      |
| GTIN                 | 4048879759915 |
| Verpakkingseenheid   | 1             |

Electrical data | Supply

|                           |        |
|---------------------------|--------|
| Operating voltage DC      | 24 V   |
| Operating voltage DC min. | 21,6 V |
| Operating voltage DC max. | 26,4 V |
| Current consumption max.  | 430 mA |

Industrial communication | HMI

|                               |                                                       |
|-------------------------------|-------------------------------------------------------|
| Buzzer sound                  | fast beep, continuous beep, fast high-low, sweep tone |
| Reduced sound pressure at 1 m | 80 dB                                                 |
| Sound pressure at 1 m         | 90 dB                                                 |

Device protection | Electrical

|                                                 |                  |
|-------------------------------------------------|------------------|
| Degree of protection (EN IEC 60529)             | IP65             |
| Additional condition protection degree          | inserted, locked |
| <b>Mechanical data   Material data</b>          |                  |
| Color housing                                   | black            |
| Material housing                                | Plastic          |
| <b>Mechanical data   Mounting data</b>          |                  |
| Height                                          | 334 mm           |
| Width                                           | 70 mm            |
| Depth                                           | 70 mm            |
| <b>Environmental characteristics   Climatic</b> |                  |
| Operating temperature min.                      | -30 °C           |
| Operating temperature max.                      | 60 °C            |