





M12 female receptable 0° D-cod. rear

4-pol., PCB pin

PCB connectors
 Female straight
 M12, 4-pole
 D-coded
 THT-solder connection
 Rear mounting

[Link naar het product](#)**Afbeelding**



Product van afwijken van afbeelding



Side 1	
Coating contact	gold plated
Family construction form	M12
Coding	D
Material contact	Copper alloy
No. of poles	4
Commerciële gegevens	
ECLASS-6.0	27279220
ECLASS-6.1	27279220
ECLASS-7.0	27440103
ECLASS-8.0	27440103
ECLASS-9.0	27440109
ECLASS-10.1	27440109
ECLASS-11.1	27440109
ECLASS-12.0	27440109
ETIM-5.0	EC001855
Douane tarief nummer	85366990
GTIN	4065909012727
Verpakkingseenheid	10
Electrical data Supply	
Operating voltage AC	250 V
Operating voltage DC	250 V
Current operating per contact max.	4 A
Industrial communication	
Transfer parameters	CAT5
Installation Connection	
Connection information	THT-solder connection
Tightening torque	0,6 Nm
Mounting set	M12 x 1
Width across flats	SW17
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP67

Additional condition protection degree	inserted, screwed
--	-------------------

Pollution Degree	3
------------------	---

Insulation resistance min.	100 MΩ
----------------------------	--------

Mechanical data | Material data

Coating locking	nickel plated
-----------------	---------------

Material housing	Copper alloy
------------------	--------------

Material contact carrier	PA66
--------------------------	------

Locking material	Copper alloy
------------------	--------------

Mechanical data | Mounting data

Mounting method	inserted, screwed, Shaking protection
-----------------	---------------------------------------

Environmental characteristics | Climatic

Operating temperature min.	-40 °C
----------------------------	--------

Operating temperature max.	85 °C
----------------------------	-------

Important installation notes

Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.
-----------------------	---

Note on bending radius	Attention: Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.
------------------------	---