

A3 Coupling h., IP65

Single locking lever m., top entry M20


A3
Coupling housing (low)
Single locking lever
IP65
Technical data will be only guaranteed with Murrelektronik components.

Link naar het product

Afbeelding



Product van afwijken van afbeelding



Commerciële gegevens

ECLASS-6.0	27279221
ECLASS-7.0	27440104
ECLASS-8.0	27440104
ECLASS-9.0	27440102
ECLASS-10.1	27440202
ECLASS-11.1	27440202
ECLASS-12.0	27440202
ETIM-5.0	EC000437
Douane tarief nummer	85389099
GTIN	4048879716826
Verpakkingseenheid	1

Installation

Cable outlet straight

Installation | Connection

Mounting set	M20
Mating cycles min.	500

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP65
Additional condition protection degree	inserted, locked, with screw connection

Mechanical data

Housing type Coupling housing

Mechanical data | Material data

Coating housing powder-coated

Coating locking	verzinkt
Material housing	Zinc die-casting
Locking material	Steel

Mechanical data | Mounting data

Size	A3
Height	60,5 mm
Width	26,6 mm
Depth	26,6 mm
Locking techniques	Single locking lever

Environmental characteristics | Climatic

Operating temperature min.	-40 °C
Operating temperature max.	100 °C
Climatic category (EN IEC 60068-1)	40/100/21