


Power female module, 2-pole, crimp t.

1000 V, 100 A


Female
2-pole
Crimp
Technical data will be only guaranteed with Murrelektronik components.

Link naar het product

Afbeelding



Product van afwijken van afbeelding



Commerciële gegevens	
ECLASS-6.0	27143424
ECLASS-6.1	27261204
ECLASS-7.0	27440204
ECLASS-8.0	27440204
ECLASS-9.0	27440217
ECLASS-10.1	27440217
ECLASS-11.1	27440217
ECLASS-12.0	27440217
ETIM-5.0	EC000438
Douane tarief nummer	85389099
GTIN	4048879641692
Verpakkingseenheid	5
Electrical data Supply	
Operating voltage AC	1000 V
Operating voltage DC	1000 V
Operating current	100 A
Installation	
Connection cross section min.	10 mm²
Connection cross section max.	35 mm²
AWG number min.	8

AWG number max. 2

Installation | Connection

Wire insulation diameter min.	13 mm
Connection	Crimp
Gender	female
Mating cycles min.	500

Installation | Pin assignment

No. of poles 2

Device protection | Electrical

Pollution Degree	3
Rated surge voltage	8 kV
Insulation resistance min.	100 MΩ
Overvoltage category (EN 60664-1)	I
Overvoltage category (EN 60950-1)	III

Mechanical data

Holding force modules min.	300 N
Pulling force max.	140 N

Mechanical data | Material data

Coating contact	silver-plated
Combustibility class (UL94)	V-0
Material housing	PA
Material contact	Brass

Mechanical data | Mounting data

Number of module slots	2
Height	53 mm
Width	13 mm
Depth	13 mm

Environmental characteristics | Climatic

Operating temperature min.	-40 °C
Operating temperature max.	125 °C
Climatic category (EN IEC 60068-1)	40/125/10